HIGH PASS FILTER
RFH1006-1606SLC

Features:

- Rugged Shielded case
- Other standard and custom HPF models
- Wide selection of cutoff frequency
- Small & Rigid design
- Economical



Description:

The RFH1006-1606SLC is a High pass filter in a shielded package fabricated using SMD LC technology. Covering 100-2000 MHz bandwidth, these units offer decent matching within the passband and high rejection in stopband.

Applications:

- Amateur Radio Equipment's
- Test and measurement equipment
- Broadcasting
- Radio Communications
- Navigations

Optional Accessories :

- Adapter Kit
- 50 Ω Termination
- Directional coupler Kit
- Antenna Kit

Electrical Specifications:

Frequency Range	100 - 2000 MHz
Power Capacity	0.5 W
Insertion Loss Cutoff @ 100 MHz	- 3 dB Max
Return Loss	-13 dB Min
VSWR	1.5:1
Input/ Output	SMA (F)
Operating Temperature	0°C - 50°C

Mechanical Specifications:

Dimensions (mm) : 	(L) = 56 (B) = 28.7 (H) = 17.4 (A) = 49 (Ø) = 19	
Shape:	Cuboidal/ Cylindrical shape	
Weight :	Cuboidal :71 gm / Cylindrical :25 gm	

S PARAMETER



Filter Kits Available:

LPF (11 TYPES)
HPF (9 TYPES)
BPF (5 TYPES)

FILTER KIT

HIGH PASS FILTER KIT

A. Electrical specification and Performance data contained in this specification document are based on RFME's applicable established test performance criteria and measurement instruction.
B. The parts covered by this specification document are subject to RFME standard limited warranty and terms & conditions.