HIGH PASS FILTER
RFH8006-1307SLC

Features:

- Rugged Shielded case
- Other standard and custom HPF models
- Wide selection of cutoff frequency
- Small & Rigid design
- Economical



Description:

The RFH8006-1307SLC is a High pass filter in a shielded package fabricated using SMD LC technology. Covering 800-5000 MHz bandwidth, these units offer decent matching within the passband and high rejection in stopband.

Applications:

- Amateur Radio Equipment's
- Test and measurement equipment
- Cellular Applications
- WiMAX

Optional Accessories :

- Adapter Kit
- Cable as per User Requirment (Figure 1)
- 50 Ω Termination
- Directional coupler Kit
- Antenna Kit



Electrical Specifications:

Frequency Range	800 - 5000 MHz
Power Capacity	0.5 W
Insertion Loss Cutoff @ 800 MHz	- 1 dB Max
Return Loss	-10 dB Min
VSWR	1.9:1
Input/ Output Connector	SMA (F)
Operating Temperature	0°C - 50°C

Mechanical Specifications:

Dimensions (mm) : 	(L) = 56 (B) = 28.7 (H) = 17.4 (A) = 49 (Ø) = 19	
Shape:	Cuboidal/ Cylindrical shape	
Weight :	Cuboidal :71 gm / Cylindrical :25 gm	



Filter Kits Available:

LPF (11 TYPES)
HPF (9 TYPES)
BPF (5 TYPES)

FILTER KIT

HIGH PASS FILTER KIT

A. Electrical specification and Performance data contained in this specification document are based on RFME's applicable established test performance criteria and measurement instruction.
B. The parts covered by this specification document are subject to RFME standard limited warranty and terms & conditions.